

# PTFE TAPE

## 50 m x 19 mm x 0.1 mm

### DESCRIPTION

Polymerized laminated Tetrafluoroethylene (PTFE).

### PROPERTIES

- Compatible with all usual pipe materials, chemicals, acids, alkalis, solvents and gases.
- Certified by WRAS (UK) for drinking water.

### APPLICATIONS

- Sealing of plastic or metallic threaded accessories in piping systems for fluids.
- Sealing of deposits and lines of fuel, air conditioning units, radiators, discharge lines and with cooling fluids, hydraulic and braking systems.
- Temperature range: from  $-20\text{ }^{\circ}\text{C}$  to  $125\text{ }^{\circ}\text{C}$ .

### TECHNICAL CHARACTERISTICS

Density	Approx. 0.52 g/mL
Thickness	0.1 mm
Length	50 m
Width	19 mm

### INSTRUCTIONS FOR USE

We recommend rolling the PTFE tape clockwise around the male thread – turns are indicated below:

Number of turns depending on the thread
1 turn minimum at thread $\frac{1}{4}$ "
2 turns minimum from $\frac{1}{4}$ " to $\frac{1}{2}$ "
3 turns minimum from $\frac{1}{2}$ " to 1"

This procedure must be undertaken with a minimum tension, so the tape adopts the shape of the thread, pulling the tape to cut it once the application is finished.

### STORAGE

Keep inside the original container in a cool, dry place, avoiding direct exposure to sunlight.

## **PRESENTATION**

Visit [www.unecol.com](http://www.unecol.com)

---

The above mentioned data are based on our better experience and knowledge, but should be understood as specifications. The end user is responsible for verifying the suitability of the information provided, according to the specific use of the product