



Schoeller Allibert



See [www.schoellerallibert.com](http://www.schoellerallibert.com) for additional material like Download Brochure

## Related Products

## Dosing Tank 250L (580 x H1083)

Item: 8929051



This roto moulded 250L dosing tank is specially designed for water treatment and integration into mixing, dosing and additive incorporation systems. Reliable, dosing tanks are manufactured in food-grade linear polyethylene, enriched with anti-ultraviolet additives. The upper section is reinforced to support stirrers and metering pumps. The upper hatch is fitted with a Ø125 watertight threaded lid so no spilling or leakage is possible. The 500 and 1000 litre models are fitted with a Ø 250 inspection hatch and have a threaded lid fitted with a Ø 20 vent. Available in the standard colour natural transparent white, other colours are available on request. User-friendly thanks to the vat with scale for instant level reading.

## Specifications

External max length (L):	580 mm
External max width (W):	580 mm
External max height (H):	1083 mm
Incremental stack height (Ha):	1083 mm
Net weight kg:	10.5 kg
Weight Tolerance:	+/-5%, unless stated otherwise
Usable Volume:	250 L
Individual Load Capacity:	475 kg
Main Material:	MDPE (Medium-Density Polyethylene)
Operational Temperature Range:	-10 °C to 40 °C

## Packaging

Units/Pallet (pc):	8
Pallet size:	1200 mm x 1000 mm
Pallet Height:	2296 mm

## Feature and Benefits

- Personnel Safety - Ensures operator safety in case of accidental spillage.
- Anti-Corrosive Protection - All main parts are made from plastic, preventing oxidation and the need for maintenance.
- Specialized Design - Specially designed for water treatment and integration into mixing, dosing, and additive systems.
- Food-Grade Material - Manufactured in food-grade linear polyethylene enriched with anti-ultraviolet additives.
- Reinforced Upper Section - The upper section is reinforced to support stirrers and metering pumps.
- Watertight Lid - The upper hatch is fitted with a watertight threaded lid to prevent spilling or leakage.
- User-Friendly Scale - Integrated user-friendly scale for instant-level readings.
- Range of Versions - Available in sizes from 50L up to 1,000L.