

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



EXT_GRE_V12-LINER REPAIR KIT

Version 1 Date of compilation: 17/02/2021

Version 6 (replaces version 5)

Revision date: 19/02/2026

Page 1 of 14

Print date: 19/02/2026

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name: LINER REPAIR KIT
Product Code: EXT_GRE_V12
UFI: QM32-KOM8-6001-6ECU

1.2 Relevant identified uses of the substance or mixture and uses advised against.

Adhesive

Uses advised against:

Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

Company: **MANUFACTURAS GRE**
Address: Aritz Bidea, 57 - Belako Industrialdea
City: 48100 Munguia - Vizcaya
Province: VIZCAYA
Telephone: Tel: +34 946 741 116
Fax: Fax: +34 946 741 708
E-mail: www.grepool.com

1.4 Emergency telephone number: +34 93 724 39 00 (Only available during office hours; Monday-Friday; 08:00-18:00)

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the substance or mixture.

In accordance with Regulation (EC) No 1272/2008:

Eye Irrit. 2 : Causes serious eye irritation.
Flam. Liq. 3 : Flammable liquid and vapour.
STOT SE 3 : May cause drowsiness or dizziness.

2.2 Label elements.

Labelling in accordance with Regulation (EC) No 1272/2008:

Pictograms:



Signal Word:

Warning

Hazard statements:

H226 Flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read carefully and follow all instructions.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P271 Use only outdoors or in a well-ventilated area.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



EXT_GRE_V12-LINER REPAIR KIT

Version 1 Date of compilation: 17/02/2021

Version 6 (replaces version 5)

Revision date: 19/02/2026

Page 2 of 14

Print date: 19/02/2026

P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/...
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER/doctor/... if you feel unwell.
P337+P313	If eye irritation persists: Get medical advice/attention.
P370+P378	In case of fire: Use... to extinguish.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container to ...

EUH statements:

EUH066 Repeated exposure may cause skin dryness or cracking.

Contains:

acetone, propan-2-one, propanone
butanone, ethyl methyl ketone
ethyl acetate
methyl acetate

2.3 Other hazards.

The mixture does not contain substances classified as PBT.

The mixture does not contain substances classified as vPvB.

The mixture does not contain any endocrine disrupting properties substances.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.

Not applicable.

3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

Identifiers	Name	Concentrate	(*)Classification - Regulation (EC) No 1272/2008	
			Classification	Specifics concentration limits and Acute toxicity estimate
Index No: 607-022-00-5 CAS No: 141-78-6 EC No: 205-500-4 Registration No: 01-2119475103-46-XXXX	[1] ethyl acetate	20 - 50 %	Eye Irrit. 2, H319 - Flam. Liq. 2, H225 - STOT SE 3, H336, EUH066	-
Index No: 606-002-00-3 CAS No: 78-93-3 EC No: 201-159-0 Registration No: 01-2119457290-43-XXXX	[1] butanone, ethyl methyl ketone	10 - 20 %	Eye Irrit. 2, H319 - Flam. Liq. 2, H225 - STOT SE 3, H336, EUH066	-
Index No: 607-021-00-X CAS No: 79-20-9 EC No: 201-185-2 Registration No: 01-2119459211-47-XXXX	methyl acetate	10 - 20 %	Eye Irrit. 2, H319 - Flam. Liq. 2, H225 - STOT SE 3, H336, EUH066	-

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



EXT_GRE_V12-LINER REPAIR KIT

Version 1 Date of compilation: 17/02/2021

Version 6 (replaces version 5)

Revision date: 19/02/2026

Page 3 of 14

Print date: 19/02/2026

Index No: 606-001-00-8 CAS No: 67-64-1 EC No: 200-662-2 Registration No: 01-2119471330-49-XXXX	[1] acetone, propan-2-one, propanone	10 - 20 %	Eye Irrit. 2, H319 - Flam. Liq. 2, H225 - STOT SE 3, H336	-
---	--------------------------------------	-----------	---	---

(*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

[1] Substance with a European Union exposure limit in the workplace (see section 8.1).

SECTION 4: FIRST AID MEASURES.

4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration. Do not administer anything orally. If unconscious, place them in a suitable position and seek medical assistance.

Eye contact.

Remove contact lenses, if present and if it is easy to do. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance. Don't let the person to rub the affected eye.

Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.

Irritant Product, repeated or prolonged contact with skin or mucous membranes can cause redness, blisters or dermatitis, inhalation of spray mist or particles in suspension may cause irritation of the respiratory tract, some symptoms may not be immediate.

Repeated or prolonged eye contact may cause stinging, tearing, redness, swelling, and blurred vision.

4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious. Cover the affected area with a dry sterile bandage. Protect the affected area from pressure or friction.

SECTION 5: FIREFIGHTING MEASURES.

Flammable product, the necessary prevention measures should be taken in order to avoid risks, In case of fire, the following measures are recommended:

5.1 Extinguishing media.

Suitable extinguishing media:

Extinguisher powder or CO₂. In case of more serious fires, also alcohol-resistant foam and water spray.

Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

5.2 Special hazards arising from the substance or mixture.

Special risks.

Exposure to combustion or decomposition products can be harmful to your health.

During a fire and depending on its magnitude the following may occur:

- Flammable vapors or gases.

5.3 Advice for firefighters.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



EXT_GRE_V12-LINER REPAIR KIT

Version 1 Date of compilation: 17/02/2021

Version 6 (replaces version 5)

Revision date: 19/02/2026

Page 4 of 14

Print date: 19/02/2026

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways. Follow the instructions given in the emergency or fire evacuation plan or plans if available.

Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots. During extinction and depending on the magnitude and proximity to the fire, additional protective equipment such as chemical protection gloves, heat-reflecting suits or gas-tight suits may be required.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.

Eliminate possible ignition points and ventilate the area. No smoking. Avoid breathing fumes. For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.

Product not classified as hazardous for the environment, avoid spillage as much as possible.

6.3 Methods and material for containment and cleaning up.

Contain and collect spillage with inert absorbent material (earth, sand, vermiculite, Kieselguhr...) and clean the area immediately with a suitable decontaminant.

Deposit waste in closed and suitable containers for disposal, in compliance with local and national regulations (see section 13).

6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.

The fumes are heavier than air and can spread across the ground. They can form explosive mixtures with air. Prevent the creation of flammable or explosive fume concentrations in the air; prevent fume concentrations above work exposure limits. The product must only be used in areas where all unprotected flames and other ignition points have been eliminated. Electrical equipment has to be protected according to applicable standards.

The product can be electrostatically charged: always use earth grounds when transferring the product. Operators must use anti-static footwear and clothing, and floors must be conductors.

Keep the container tightly closed and isolated from heat sources, sparks, and fire. Do not use tools that can cause sparks. For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 25 °C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorized persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

The product is not affected by Directive 2012/18/EU (SEVESO III).

7.3 Specific end use(s).

Not available.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

8.1 Control parameters.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



EXT_GRE_V12-LINER REPAIR KIT

Version 1 Date of compilation: 17/02/2021

Version 6 (replaces version 5)

Revision date: 19/02/2026

Page 5 of 14

Print date: 19/02/2026

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m ³
ethyl acetate	141-78-6	European Union [1]	Eight hours	200	734
			Short term	400	1468
butanone, ethyl methyl ketone	78-93-3	European Union [1]	Eight hours	200	600
			Short term	300	900
acetone, propan-2-one, propanone	67-64-1	European Union [1]	Eight hours	500	1210
			Short term		

[1] According both Binding Occupational Exposure Limits (BOELVs) and Indicative Occupational Exposure Limits (IOELVs) adopted by Scientific Committee for Occupational Exposure Limits to Chemical Agents (SCOEL).

The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Type	Value
ethyl acetate CAS No: 141-78-6 EC No: 205-500-4	DNEL (Workers)	Inhalation, Chronic, Systemic effects	734 (mg/m ³)
	DNEL (Workers)	Inhalation, Chronic, Local effects	734 (mg/m ³)
	DNEL (Consumers)	Inhalation, Chronic, Local effects	367 (mg/m ³)
	DNEL (Workers)	Inhalation, Short term, Local effects	1468 (mg/m ³)
	DNEL (Consumers)	Inhalation, Short term, Local effects	734 (mg/m ³)
	DNEL (Workers)	Dermal, Chronic, Systemic effects	63 (mg/kg bw/day)
	DNEL (Consumers)	Dermal, Chronic, Systemic effects	37 (mg/kg bw/day)
butanone, ethyl methyl ketone CAS No: 78-93-3 EC No: 201-159-0	DNEL (Workers)	Inhalation, Chronic, Systemic effects	600 (mg/m ³)
	DNEL (Consumers)	Inhalation, Chronic, Systemic effects	106 (mg/m ³)
	DNEL (Workers)	Dermal, Chronic, Systemic effects	1161 (mg/kg bw/day)
	DNEL (Consumers)	Dermal, Chronic, Systemic effects	412 (mg/kg bw/day)
	DNEL (Consumers)	Oral, Chronic, Systemic effects	31 (mg/kg bw/day)
	DMEL (Consumers)	Inhalation, Chronic, Systemic effects	106 (mg/m ³)
	DMEL (Consumers)	Dermal, Chronic, Systemic effects	412 (mg/m ³)
methyl acetate CAS No: 79-20-9 EC No: 201-185-2	DNEL (Workers)	Inhalation, Chronic, Local effects	305 (mg/m ³)
	DNEL (Workers)	Inhalation, Chronic, Systemic effects	610 (mg/m ³)
acetone, propan-2-one, propanone CAS No: 67-64-1 EC No: 200-662-2	DNEL (Workers)	Inhalation, Chronic, Systemic effects	1210 (mg/m ³)
	DNEL (Consumers)	Inhalation, Chronic, Systemic effects	200 (mg/m ³)
	DNEL (Workers)	Inhalation, Short term, Local effects	2420 (mg/m ³)
	DNEL (Workers)	Dermal, Chronic, Systemic effects	186 (mg/kg bw/day)
	DNEL (Consumers)	Dermal, Chronic, Systemic effects	62 (mg/kg bw/day)

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



EXT_GRE_V12-LINER REPAIR KIT

Version 1 Date of compilation: 17/02/2021

Version 6 (replaces version 5)

Revision date: 19/02/2026

Page 6 of 14

Print date: 19/02/2026

	DNEL (Consumers)	Oral, Chronic, Systemic effects	62 (mg/kg bw/day)
--	---------------------	---------------------------------	----------------------

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

Concentration levels PNEC:

Name	Details	Value
ethyl acetate CAS No: 141-78-6 EC No: 205-500-4	aqua (freshwater)	0,24 (mg/L)
	aqua (marine water)	0,024 (mg/L)
	aqua (intermittent releases)	1,65 (mg/L)
	sediment (freshwater)	1,15 (mg/L)
	sediment (marine water)	0,115 (mg/L)
	Soil	0,148 (mg/kg soil dw)
	STP	650 (mg/L)
	oral (Hazard for predators)	0,2 (g/kg food)
butanone, ethyl methyl ketone CAS No: 78-93-3 EC No: 201-159-0	aqua (freshwater)	55,8 (mg/L)
	aqua (marine water)	55,8 (mg/L)
	Soil	22,5 (mg/kg soil dw)
	aqua (intermittent releases)	55,8 (mg/L)
	STP	709 (mg/L)
	sediment (freshwater)	284,74 (mg/kg sediment dw)
	sediment (marine water)	284,7 (mg/kg sediment dw)
oral (Hazard for predators)	1000 (mg/kg food)	
acetone, propan-2-one, propanone CAS No: 67-64-1 EC No: 200-662-2	aqua (freshwater)	10,6 (mg/L)
	aqua (marine water)	1,06 (mg/L)
	aqua (intermittent releases)	21 (mg/L)
	STP	100 (mg/L)
	sediment (freshwater)	30,04 (mg/kg sediment dw)
	sediment (marine water)	3,04 (mg/kg sediment dw)
	soil	29,5 (mg/kg soil dw)

PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.

8.2 Exposure controls.

Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	100 %
Uses:	Adhesive
Breathing protection:	

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



EXT_GRE_V12-LINER REPAIR KIT

Version 1 Date of compilation: 17/02/2021

Version 6 (replaces version 5)

Revision date: 19/02/2026

Page 7 of 14

Print date: 19/02/2026

PPE:	Filter mask for protection against gases and particles.				
Characteristics:	«CE» marking, category III. The mask must have a wide field of vision and an anatomically designed form in order to be sealed and watertight.				
CEN standards:	EN 136, EN 140, EN 405				
Maintenance:	Should not be stored in places exposed to high temperatures and damp environments before use. Special attention should be paid to the state of the inhalation and exhalation valves in the face adaptor.				
Observations:	Read carefully the manufacturer's instructions regarding the equipment's use and maintenance. Attach the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols: P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer.				
Filter Type needed:	A2				
Hand protection:					
PPE:	Protective gloves.				
Characteristics:	«CE» marking, category II.				
CEN standards:	EN 374-1, En 374-2, EN 374-3, EN 420				
Maintenance:	Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.				
Observations:	Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands.				
Material:	PVC (polyvinyl chloride)	Breakthrough time (min.):	> 480	Material thickness (mm):	0,35
Eye protection:					
PPE:	Face shield.				
Characteristics:	«CE» marking, category II. Face and eye protector against splashing liquid.				
CEN standards:	EN 165, EN 166, EN 167, EN 168				
Maintenance:	Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions. Make sure that mobile parts move smoothly.				
Observations:	Face shields should offer a field of vision with a dimension in the central line of, at least, 150 mm vertically once attached to the frame.				
Skin protection:					
PPE:	Anti-static protective clothing.				
Characteristics:	«CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements.				
CEN standards:	EN 340, EN 1149-1, EN 1149-2, EN 1149-3, EN 1149-5				
Maintenance:	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.				
Observations:	The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use.				
PPE:	Anti-static safety footwear.				
Characteristics:	«CE» marking, category II.				
CEN standards:	EN ISO 13287, EN ISO 20344, EN ISO 20346				
Maintenance:	The footwear should be checked regularly				
Observations:	The level of comfort during use and acceptability are factors that are assessed very differently depending on the user. Therefore, it is advisable to try on different footwear models and, if possible, different widths.				

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.

Physical state: Liquid

Colour: Colorless to slight yellow

Odour: Solvent odour

Odour threshold: Not applicable/Not available due to the nature/properties of the product

Melting point: -73.5 °C

Freezing point: Not applicable/Not available due to the nature/properties of the product

Boiling point or initial boiling point and boiling range: >=70 °C

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



EXT_GRE_V12-LINER REPAIR KIT

Version 1 Date of compilation: 17/02/2021

Version 6 (replaces version 5)

Revision date: 19/02/2026

Page 8 of 14

Print date: 19/02/2026

Flammability: Highly flammable liquid and vapour
Lower explosion limit: 1.2 vol %
Upper explosion limit: 7.5 vol %
Flash point: <=23 °C
Auto-ignition temperature: 408 °C
Decomposition temperature: Not applicable/Not available due to the nature/properties of the product
pH: Not applicable/Not available due to the nature/properties of the product
Kinematic viscosity: Not applicable/Not available due to the nature/properties of the product
Solubility: Insoluble in water. Soluble in most organic solvents.
Hydrosolubility: Not applicable/Not available due to the nature/properties of the product
Liposolubility: Not applicable/Not available due to the nature/properties of the product
Partition coefficient n-octanol/water (log value): Not applicable/Not available due to the nature/properties of the product
Vapour pressure: 139,756 (Estimation based on the indication of the Regulation (CE) N°1272/2008.)
Absolute density: Not applicable/Not available due to the nature/properties of the product
Relative density: 0.75
Relative vapour density: Not applicable/Not available due to the nature/properties of the product
Particle characteristics: Not applicable/Not available due to the nature/properties of the product

9.2 Other information

Information with regard to physical hazard classes

Flammable liquids:

Sustained combustibility: Yes.

SECTION 10: STABILITY AND REACTIVITY.

10.1 Reactivity.

The product does not present hazards by their reactivity.

10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

10.3 Possibility of hazardous reactions.

Flammable liquid and vapour.

10.4 Conditions to avoid.

Avoid any improper handling.

10.5 Incompatible materials.

Keep away from oxidising agents and from highly alkaline or acidic materials in order to prevent exothermic reactions.

10.6 Hazardous decomposition products.

No decomposition if used for the intended uses.

SECTION 11: TOXICOLOGICAL INFORMATION.

IRRITANT MIXTURE. Splashes in the eyes can cause irritation.

IRRITANT MIXTURE. The inhalation of spray mist or suspended particulates can irritate the respiratory tract. It can also cause serious respiratory difficulties, central nervous system disorders, and in extreme cases, unconsciousness.

11.1 Information on hazard classes as defined in Regulation (EC) N° 1272/2008.

Repeated or prolonged eye contact may cause stinging, tearing, redness, swelling, and blurred vision.

Toxicological information about the substances present in the composition.

Name	Acute toxicity			
	Type	Test	Kind	Value
butanone, ethyl methyl ketone	Oral	LD50	Rat	2740 mg/kg bw [1]
		[1] Toxicology and Applied Pharmacology. Vol. 19, Pg. 699, 1971		
butanone, ethyl methyl ketone	Dermal	LD50	Rabbit	6480 mg/kg bw [1]
		[1] Shell Chemical Company. Vol. MSDS-5390-4		

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



EXT_GRE_V12-LINER REPAIR KIT

Version 1 Date of compilation: 17/02/2021

Version 6 (replaces version 5)

Revision date: 19/02/2026

Page 9 of 14

Print date: 19/02/2026

CAS No: 78-93-3	EC No: 201-159-0	Inhalation	
acetone, propan-2-one, propanone		Oral	LD50 Rat 5800 mg/kg bw [1] [1] Journal of Toxicology and Environmental Health. Vol. 15, Pg. 609, 1985
		Dermal	
		Inhalation	
CAS No: 67-64-1	EC No: 200-662-2		

a) acute toxicity;
Not conclusive data for classification.

b) skin corrosion/irritation;
Not conclusive data for classification.

c) serious eye damage/irritation;
Product classified:
Eye irritation, Category 2: Causes serious eye irritation.

d) respiratory or skin sensitisation;
Not conclusive data for classification.

e) germ cell mutagenicity;
Not conclusive data for classification.

f) carcinogenicity;
Not conclusive data for classification.

g) reproductive toxicity;
Not conclusive data for classification.

h) STOT-single exposure;
Product classified:
Specific target organ toxicity following a single exposure, Category 3: May cause drowsiness or dizziness.

i) STOT-repeated exposure;
Not conclusive data for classification.

j) aspiration hazard;
Not conclusive data for classification.

11.2 Information on other hazards.

Endocrine disrupting properties

This product does not contain components with endocrine-disrupting properties with effects on human health.

Other information

There is no information available on other adverse health effects.

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.

Name	Ecotoxicity			
	Type	Test	Kind	Value
ethyl acetate	Fish	LC50	Pimephales promelas	230 mg/l (96 h) [1]
				[1] US EPA method E03-05, 1984

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



EXT_GRE_V12-LINER REPAIR KIT

Version 1 Date of compilation: 17/02/2021

Version 6 (replaces version 5)

Revision date: 19/02/2026

Page 10 of 14

Print date: 19/02/2026

CAS No: 141-78-6 EC No: 205-500-4	Aquatic invertebrates	EC50 Hydra Oligactis (Hydrozoa) 1350 mg/l (48 h) [1] [1] Aquat. Toxicol. 4, 73 - 82, Slooff, W. 1983
	Aquatic plants	EC50 Algae 2500 mg/l (96 h) [1] [1] Slooff, W. 1982. A Comparative Study on the Short-Term Effects of 15 Chemicals on Fresh Water Organisms of Different Tropic Levels. Natl.Tech.Inf.Serv., Springfield, VA :25 p. (DUT) (ENG ABS) (NTIS/PB83-200386)
butanone, ethyl methyl ketone CAS No: 78-93-3 EC No: 201-159-0	Fish	LC50 Pimephales promelas 2993 mg/l (96 h) [1] [1] Experimental result, 1998.
	Aquatic invertebrates	LC50 Daphnia magna 8890 mg/l (24 h) [1] [1] Experimental result, 1977.
	Aquatic plants	EC50 Pseudokirchnerella subcapitata 2029 mg/l (96 h) [1] [1] OECD Guideline 201 (Alga, Growth Inhibition Test) reliability based in 2006 guideline.
acetone, propan-2-one, propanone CAS No: 67-64-1 EC No: 200-662-2	Fish	LC50 Fish 8300 mg/l (96 h) [1] [1] Cairns, J.Jr., and A. Scheier 1968. A Comparison of the Toxicity of Some Common Industrial Waste Components Tested Individually and Combined. Prog.Fish-Cult. 30(1):3-8
	Aquatic invertebrates	LC50 Crustacean 8450 mg/l (48 h) [1] [1] Cowgill, U.M., and D.P. Milazzo 1991. The Sensitivity of Ceriodaphnia dubia and Daphnia magna to Seven Chemicals Utilizing the Three-Brood Test. Arch.Environ.Contam.Toxicol. 20(2):211-217. Canton, J.H., and D.M.M. Adema 1978. Reproducibility of Short-Term and Reproduction Toxicity Experiments with Daphnia magna and Comparison of the Sensitivity of Daphnia magna with Daphnia pulex and Daphnia cucullata in Short-Term Experiments. Hydrobiologia 59(2):135-140 (Used Reference 2018)
	Aquatic plants	EC50 Algae 7200 mg/l (96 h) [1] [1] Slooff, W. 1982. A Comparative Study on the Short-Term Effects of 15 Chemicals on Fresh Water Organisms of Different Tropic Levels. Natl.Tech.Inf.Serv., Springfield, VA :25 p. (DUT) (ENG ABS) (NTIS/PB83-200386)

12.2 Persistence and degradability.

No information is available regarding the biodegradability of the substances present.

No information is available on the degradability of the substances present.

No information is available about persistence and degradability of the product.

The surfactants contained in this product fulfill the biodegradability criteria stipulated in Regulation (EC) No. 648/2004 on detergents. The data that justifies this affirmation is available to the competent authorities that request it.

12.3 Bioaccumulative potential.

Information about the bioaccumulation of the substances present.

Name	Bioaccumulation			
	Log Pow	BCF	NOECs	Level
ethyl acetate	0,73	-	9,65 mg/L	Very low

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



EXT_GRE_V12-LINER REPAIR KIT

Version 1 Date of compilation: 17/02/2021

Version 6 (replaces version 5)

Revision date: 19/02/2026

Page 11 of 14

Print date: 19/02/2026

CAS No: 141-78-6	EC No: 205-500-4				
butanone, ethyl methyl ketone		0,29	-	-	Very low
CAS No: 78-93-3	EC No: 201-159-0				
methyl acetate		0,18	-	-	Very low
CAS No: 79-20-9	EC No: 201-185-2				
acetone, propan-2-one, propanone		-0,24	3	-	Very low
CAS No: 67-64-1	EC No: 200-662-2				

12.4 Mobility in soil.

No information is available about the mobility in soil.
The product must not be allowed to go into sewers or waterways.
Prevent penetration into the ground.

12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

12.6 Endocrine disrupting properties.

This product doesn't contain components with environmental endocrine disrupting properties.

12.7 Other adverse effects.

The product is not affected by the Regulation (EU) 2024/590 of the European Parliament and of the Council of 7 February 2024 on substances that deplete the ozone layer.

No information is available about other adverse effects for the environment.

SECTION 13: DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

Land: Transport by road: ADR, Transport by rail: RID.

Transport documentation: Consignment note and written instructions

Sea: Transport by ship: IMDG.

Transport documentation: Bill of lading

Air: Transport by plane: ICAO/IATA.

Transport document: Airway bill.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



EXT_GRE_V12-LINER REPAIR KIT

Version 1 Date of compilation: 17/02/2021

Version 6 (replaces version 5)

Revision date: 19/02/2026

Page 12 of 14

Print date: 19/02/2026

14.1 UN number or ID number.

UN No: UN1133

14.2 UN proper shipping name.

Description:

ADR/RID: UN 1133, ADHESIVES (CONTAINS BUTANONE ETHYL METHYL KETONE / ACETONE PROPAN-2-ONE PROPANONE / ETHYL ACETATE), 3, PG I, (D/E)

IMDG: UN 1133, ADHESIVES (CONTAINS BUTANONE ETHYL METHYL KETONE / ACETONE PROPAN-2-ONE PROPANONE / ETHYL ACETATE), 3, PG I (23°C)

ICAO/IATA: UN 1133, ADHESIVES (CONTAINS BUTANONE ETHYL METHYL KETONE / ACETONE PROPAN-2-ONE PROPANONE / ETHYL ACETATE), 3, PG I

14.3 Transport hazard class(es).

Class(es): 3

14.4 Packing group.

Packing group: I

14.5 Environmental hazards.

Marine pollutant: No

Transport by ship, FEM – Emergency sheets (F – Fire, S - Spills): F-E,S-D

14.6 Special precautions for user.

Labels: 3



Hazard number: 33

Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR.

Proceed in accordance with point 6.

ADR LQ: 500 ml

IMDG LQ: 500 ml

ICAO LQ: 0

14.7 Maritime transport in bulk according to IMO instruments.

The product is not transported in bulk.

SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

Volatile organic compound (VOC)

VOC content (p/p): 86 %

VOC content: 645 g/l

Contains in accordance with Regulation (EC) No 648/2004 on detergents:

perfumes

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

Kind of pollutant to water (Germany): WGK 1: Slightly hazardous to water. (Autoclassified according to the AwSV Regulations)

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



EXT_GRE_V12-LINER REPAIR KIT

Version 1 Date of compilation: 17/02/2021

Version 6 (replaces version 5)

Revision date: 19/02/2026

Page 13 of 14

Print date: 19/02/2026

Information on Annex I of Commission Delegated Regulation (EU) 2020/1737 of 14 July 2020 and Annex I of Regulation (EC) No. 273/2004 of the European Parliament and of the Council of 11 February 11 2004 on drug precursors:

CAS No	Name	Category
67-64-1	acetone; propan-2-one; propanone	3
78-93-3	butanone; ethyl methyl ketone	3

Annex I: List of scheduled substances.

Information on Annex I and Annex II of Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 20 2019 on the marketing and use of explosives precursors:

CAS No	Name	Annex
67-64-1	acetone; propan-2-one; propanone	II

Annex I: Restricted explosives precursor.

Annex II: Reportable explosives precursors.

15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Complete text of the EUH phrases that appear in section 3:

EUH066	Repeated exposure may cause skin dryness or cracking.
--------	---

Classification codes:

Eye Irrit. 2: Eye irritation, Category 2
Flam. Liq. 2: Flammable liquid, Category 2
Flam. Liq. 3: Flammable liquid, Category 3
STOT SE 3: Specific target organ toxicity following a single exposure, Category 3

Changes regarding to the previous version:

- Change in the hazard classification (SECTION 2.1).
- Removal of precautionary statements/hazard statements/pictograms/signal word (SECTION 2.2).
- Addition of precautionary statements/hazard statements/pictograms/signal word (SECTION 2.2).
- Changes in the composition of the product (SECTION 3.2).
- Modifications in the handling and storage precautions (SECTION 7.1).
- Modifications in the handling and storage precautions (SECTION 7.2).
- Modification in the values of the physical and chemical properties (SECTION 9).
- Modification of the information of the stability and reactivity conditions (SECTION 10.3).
- Modification of the information of the stability and reactivity conditions (SECTION 10.4).
- Modification of the information of the stability and reactivity conditions (SECTION 10.5).
- Modification of the information of the stability and reactivity conditions (SECTION 10.6).
- Change in the hazard classification (SECTION 11.1).
- Modification of the classification ADR/IMDG/ICAO/IATA/RID (SECTION 14).
- National legislative changes (SECTION 15.1).

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards	On basis of test data
Health hazards	Calculation method

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



EXT_GRE_V12-LINER REPAIR KIT

Version 1 Date of compilation: 17/02/2021

Version 6 (replaces version 5)

Revision date: 19/02/2026

Page 14 of 14

Print date: 19/02/2026

Environmental hazards Calculation method

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Abbreviations and acronyms used:

- ADR: Agreement concerning the International Carriage of Dangerous Goods by Road.
- AwSV: Facility Regulations for handling substances that are hazardous for the water.
- BCF: Bioconcentration factor.
- CEN: European Committee for Standardization.
- DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.
- DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.
- EC50: Half maximal effective concentration.
- PPE: Personal protection equipment.
- IATA: International Air Transport Association.
- ICAO: International Civil Aviation Organization.
- IMDG: International Maritime Code for Dangerous Goods.
- LC50: Lethal concentration, 50%.
- LD50: Lethal dose, 50%.
- NOEC: No observed effect concentration.
- PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.
- RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.
- WGK: Water hazard classes.

Key literature references and sources for data:

- <http://eur-lex.europa.eu/homepage.html>
- <http://echa.europa.eu/>
- Regulation (EU) 2020/878.
- Regulation (EC) No 1907/2006.
- Regulation (EC) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemical substances and mixtures (REACH).

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.